



TR5 MULTIFUNCTION PROFILE transom/self-standing

Wall fixing plate
Fe **FIP.TR5M.NKS**

6

Drilled base
Fe **BAS.TR5T.NKS**

6

Al **TR5**
TR5.1000.NAT
TR5.2000.NAT
TR5.3000.LUX*
TR5.3000.NAT
TR5.3000.NOX*

USE WITH PANELS

Slab gasket
GRN.TR5A.TRA

slab from 3 to 4,5 mm

slab up to 6,5 mm

Milling on panel for insertion

Step drill bit for PR5 inner joint

PSV.08X4.GRE

90° INNER JOINTS on TR5 with two different connections:

sliding fit

Fe **PR5.AT30.ZIN**

Fe **PR5.AS30.ZIN**

for slotted profile

Fe **PR5.CR30.ZIN**

available in 2014

Fe **PR5.2CR3.ZIN**

45 45

45 45

LMK - TR5

RMS, RMC - TR5

45 42

RDC - TR5

FDC - TR5

45 43

LMK with HLE - TR5

RMC with TCN - TR5

45 42

RDC with RD2 - TR5

FDC with RD2 - TR5

45 45

45 45

RDC - TR5

TR5 - TR5

Slotted profile - TR5



FLOOR - CEILING expansion COMPOSITIONS with CENTRAL accessories on SLOTTED PROFILE

'BRAVO EXPANDED' - realized with RMS

